






VERTICAL FEED, DEEP ACCESS WEDGES for WESTBOND WIRE BONDER



□ This design is mechanically and ultrasonically optimized for the Westbond vertical feed wire bonders.



□ Gaiser Proprietary Black Cermet Tip Material: Provides aggressive ultrasonic energy transfer and long life for sensitive material bonding applications.

- GaAs
- InP
- Small Gold Wire
- Small Pad

How to Order:

4845-MX-1520-3/4-CG-F-BKCER

Series &

Wire Feed Angle:

4845, 4852, 4860

Tip Configuration:

MX = Maxiguide, Pocket Type

VN = V-Notch, Open Notch

Other & specialized configurations available

Hole Size & Bond Length:

XX = 0.00XX in.

15 = 0.0015 in./38µm

20 = 0.0020 in./51µm

Specify in Part Number

Tip Material:

WC = Standard, No Need to Specify

TiC = Titanium Carbide

BKCER = Black Cermet

Bond Foot Options:

-CG = Cross Groove

-F = Flat Face

(Concave Standard, No Need to Specify)

Tool Length:

-625 = 0.625 in./15.88mm

-3/4 = 0.750 in./19.05mm

-L = 0.828 in./21.03mm



BITA ELECTRONIQUE S.A., 45 Rte d'Arlon, LU-1140 LUXEMBOURG VILLE

Ph. +352 450010, Fx. +352 332643, www.bit.lu, e-mail: info@bita.lu

BITA ELEKTRONIK SVENSKA AB, POB 3434, SE-10368 STOCKHOLM, Sweden

Ph. +46 (8) 319000, Fx. +46 (8) 326064, www.bit.se, e-mail: info@bita.se