

The chart below represents several example part numbers for a variety of pitches and wire diameters. These capillaries are useful for small ball, medium to fine pitch applications.

| PITCH in./μm | WIRE DIAMETER in./μm | PART NUMBER |
|--|--|--|
| .006/150 to .007/170 | .0009/23 to .0010/25 | 1551-13-437GM-70(3-F-25)20D |
| | | 1551-13-437GM-70(2.5-8D-15)20D |
| | | 1551-15-437GM-70(3.5-8D-15)20D |
| | | 1551-13-437GM-65(3.5-8D-15)20D |
| | .0010/25 | 1551-15-437GM-65(3.5-8D-15)20D |
| | | 1551-15-437GM-65(3.5-F-25)20D |
| | | 1551-15-437GM-65(4-8D-15)20D |
| | .0012/30 to .0013/33 | 1551-18-437GM-65(4-8D-15)20D |
| .005/125 to .006/150 | .0009/23 to .0010/25 | 1551-13-437GM-60(3-F-20)20D |
| | | 1551-13-437GM-59(3-8D-15)20D |
| | | 1551-13-437GM-59(4-8D-15)20D |
| | .0010/25 | 1551-15-437GM-59(4-8D-15)20D |
| | | 1551-15-437GM-59(4-8D-15)20D-AB10x10 |
| | .0011/28 to .0012/30 | 1551-17-437GM-59(3.5-8D-15)20D |
| | | 1551-17-437GM-59(3.5-8D-15)20D-AB10x10 |
| | .0012/30 to .0013/33 | 1551-18-437GM-59(4-8D-15)20D |
| 1551-18-437GM-59(4-8D-15)20D-AB10x10 | | |
| .0043/110 to .005/125 | .0009/23 to .0010/25 | 1551-13-437GM-55(3-F-20)20D |
| | | 1551-13-437GM-55(3-8D-15)20D |
| | | 1551-13-437GM-55(4-8D-15)20D |
| | .0010/25 | 1551-15-437GM-55(4-8D-15)20D |
| | | 1551-15-437GM-55(4-8D-15)20D-AB10x10 |
| | .0011/28 to .0012/30 | 1551-17-437GM-55(3.5-8D-15)20D |
| | | 1551-17-437GM-55(3.5-8D-15)20D-AB10x10 |
| | .0012/30 to .0013/33 | 1551-18-437GM-55(4-8D-15)20D |
| 1551-18-437GM-55(4-8D-15)20D-AB10x10 | | |
| .004/100 | .0010/25 | 1551-13-437GM-49(3-F-17)20D |
| | | 1551-13-437GM-50(3-8D-15)20D |
| | | 1551-15-437GM-50(3-8D-15)20D |
| | | 1551-15-437GM-50(3.5-8D-15)20D |
| | | 1551-15-437GM-50(3.5-8D-15)20D-AB10x10 |
| | .0012/30 to .0013/33 | 1551-17-437GM-50(3.5-8D-15)20D |
| | | 1551-18-437GM-50(4-8D-15)20D |
| | | 1551-18-437GM-50(4-8D-15)20D-AB10x10 |