

Heated work stage-height adjustable-Vacuum **HP-60-xx**

- .. heated area: 60 mm \varnothing
- .. temperature up to 250°C
- .. vacuum or mechanical fixturing



Technical Data and Options HP-60-xx:

Model	HP-60-250	HP-60-250/40
Heated Area	60 mm	60 mm
Temperature Range	room temperature up to 250°C	room temperature up to 250°C
Power Supply	240 V, 125 Watt	40 Volt, 80 Watt
Dimensions	\varnothing 80mm total	\varnothing 80mm total
Height	adjustable 66-78 mm	adjustable 66-78 mm
Weight	0,6 kg	0,6 kg
external Temperature Controller	HC-240	HC-40
Option	Wafflepack- Holder	Wafflepack- Holder

Temperature Controllers



HC-40



HC-240

Technical Data temperature controller for HP-60, HP-90:

Model	HC-40	HC-240
Power Supply	240 V, 50 Hz	240 V, 50 Hz
Temperature range	room temperature up to 350°C	room temperature up to 350°C
Temperature range optional	room temperature up to 1000°C	room temperature up to 1000°C
Outlet	40 V, 160 W	240 V, 2000 W
Dimensions	145 mm x 145 mm x 50 mm	145 mm x 145 mm x 50 mm
Weight	~0,5 kg	~0,5 kg